



# SOUNDMASTER PRO 4.5MM RESILIENT UNDERLAY

## SPECIFICATION DATASHEET

PRODUCT	INFORMATION
Application	Whiteriver Cork Rubber Underlay is a resilient underlay product designed for improving impact sound insulation. The underlay can be used under laminate flooring, engineered flooring, ceramic tiles (not for wet areas) and reduces unwanted transmitted noise. It is suited for use in a wide range of applications.
Material	Made from cork and recycled rubber and bonded with an isocyanate and polyol based binder for cork granulates. Contains no solvents or plasticizers.
Colour	Beige and Black with granular textured surface.
DIMENSIONS	INFORMATION
Roll Size	10m <sup>2</sup>
Length	10mt (Tolerance +/-2.0%)
Width	1000mm (Tolerance +/- 2.0%)
Thickness	Available in 3mm and 4.5mm
Density	circa. 700 kg/m <sup>3</sup>
TECHNICAL	INFORMATION
Tensile strength	> 600Kpa
Thermal conductivity	0.075 m <sup>2</sup> K/W
Thermal resistance	0.025 m <sup>2</sup> K/W
Boiling Water	No disintegration
Compression	25-35%
Recovery	> 85%
Flammability rating	Efl (EN 13501)
INSTALLATION	INFORMATION
Impact sound improvement	18dB per EN ISO 717-2
Installation	Installation to be carried out per installation instructions.

*The grading image used in this datasheet is intended only as a guide of what the final product may look like. No rights can be taken from it. This technical data sheet was developed by Whiteriver Group, Cluide, Dunleer, Co Louth, Ireland, A92 V8YN. At the time of issuing this datasheet, all information is correctly stated. The company reserves the right to update or amend the specifications of this product at any time without prior notice to third parties.*