Bona Oil Care

Technical data sheet

Bona Care Oil is a rapid drying maintenance oil for protecting and reviving oiled wooden floors. Consists of a low-viscous blend of different vegetable oils with excellent penetration ability. Replenishes the wood pores for sustained protection. Available in Neutral as well as White and Grey for intense revival of previously pigmented surfaces.

- Restores and protects
- · Low viscosity oil with good workability
- Low in VOC (<8%) and odour
- Safe for application on children's toys and countertops, EN 71-3 compliant

Technical data

Product base: Modified vegetable oils Colours: Neutral, White and Grey

VOC: <8%

Dilution: Do not dilute
Drying time: Minimum 12 hours*

*under normal indoor conditions, 20 ℃/60% R.H. Ensure proper

ventilation.

Application tool: Bona WoolPad or white pad

Consumption: 50-100 m² depending on condition of floor

Safety: Unclassified

Fire risk: Non flammable. Risk of self ignition, see safety data sheet for

more information.

Cleaning: Clean tools with white spirit. Dried material can be removed with

white spirit.

Shelf life: 3 years, from the date of production, in unopened original

container

Storage/transport: The temperature must not fall below +5°C or exceed +25°C

during storage and transport.

Disposal: Wastes and emptied containers should be handled in

accordance with local regulations.

Packaging: Neutral; 6x1 litre (plastic bottle) & 2x5 litres (tin can)

White & Grey; 6x1 litre (tin can)

Preparations

If necessary, the previously oiled surface must be thoroughly cleaned using Bona Oil Soap or the Bona DeepClean W and allowed to dry before applying maintenance oil. Allow product to reach room temperature and shake the container thoroughly before use. Pigmented versions must be carefully stirred. **Minimum temperature for use is 16°C**.

Application

- 1. Distribute the oil thinly on a section of the floor using a Bona WoolPad or a white pad fitted under a buffing machine.
- 2. Buff the treated section with cotton cloths and let dry.

WARNING: BONA OIL CARE CONTAINS DRYING OILS. RISK OF SELF-IGNITION. USED CLOTHS, RAGS, WOOL PADS AND SIMILAR MATERIAL SHOULD BE PLACED IN WATER OR SEALED METAL CONTAINERS.







Bona Oil Care

Technical data sheet

Bona Care

Maintenance

Clean the floor regularly using a dry mop and/or a vacuum cleaner. When needed, wipe off with a damp mop with Bona Oil Soap added to the cleaning water. Always clean using as dry a method as possible. Apply Bona Oil Care frequently to ensure that the pores of the wood remain saturated and unable to pick up dirt and moisture. The frequency of this operation is determined by the level of wear and may range from every 3rd year in a domestic environment to a few times a year in a commercial environment.

Detailed maintenance instructions are available at www.bona.com

The information provided is prepared to the best of our current knowledge and makes no claim to be complete. User is responsible for establishing that the product and recommendations herein are fit for the designated purpose, wood type and present situation before use. Bona can only guarantee the delivered product. A professional and thereby successful application of the product is beyond our control. If in doubt make a preliminary test or contact Bona's technical service. User is required to read and understand all information contained on package labels and safety data sheets before using this product.

