



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaBond® Rapid DPM

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited
Watchmead Welwyn Garden City
Hertfordshire. AL7 1BQ
Telephone : +44 (0)1707 394444
Telefax : +44 (0)1707 329129
E-mail address of person : EHS@uk.sika.com
responsible for the SDS

1.4 Emergency telephone number

+44 (0)1707 363899 (available during office hours).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)



Hazard pictograms :



Signal word : Danger

Hazard statements :

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements :

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

Prevention:

P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P284	In case of inadequate ventilation wear respiratory protection.

Response:

P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.

Storage:

P405	Store locked up.
------	------------------

Disposal:

P501	Dispose of contents/container in accordance with local regulation.
------	--

Hazardous components which must be listed on the label:

- 4,4'-methylenediphenyl diisocyanate
- Diphenylmethanediisocyanate, isomeres and homologues
- Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro-.omega.-hydroxy-, polymer with 1,1'-methylenebis[isocyanatobenzene]
- Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(pisocyanatobenzyl) phenyl isocyanate
- Benzene, 1,1'-methylenebis[4-isocyanato-,homopolymer, polymer with 1,2-



ethanediamine, methyloxirane and oxirane

Additional Labelling

EUH204 Contains isocyanates. May produce an allergic reaction.
 Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
 Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
 This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
4,4'-methylenediphenyl diisocyanate	101-68-8 202-966-0 01-2119457014-47-XXXX	Acute Tox. 4; H332 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT RE 2; H373	>= 10 - < 20
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9 Not Assigned	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373	>= 10 - < 20
Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro.-omega.-hydroxy-, polymer with 1,1'-methylenebis[isocyanatobenzene]	39420-98-9 Not Assigned	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373	>= 10 - < 20



Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(pisocyanatobenzyl) phenyl isocyanate	Not Assigned 905-806-4 01-2119457015-45-XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373	>= 10 - < 20
Benzene, 1,1'-methylenebis[4-isocyanato-,homopolymer, polymer with 1,2-ethanediamine, methyloxirane and oxirane	Not Assigned Not Assigned Polymer	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373	>= 10 - < 20

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Asthmatic appearance
Cough
Respiratory disorder
Allergic reactions
Excessive lachrymation
Erythema
Headache
Dermatitis
See Section 11 for more detailed information on health effects



and symptoms.

Risks : irritant effects
sensitising effects

Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause respiratory irritation.
Suspected of causing cancer.
May cause damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.



6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.



SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0,02 mg/m3 (NCO)	GB EH40
Further information	<p>Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological, irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even to tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. 54 Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified asthmagens or respiratory sensitisers., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma.</p>			
		STEL	0,07 mg/m3 (NCO)	GB EH40
Further information	<p>Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological, irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even to tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. 54 Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified asthmagens or respiratory sensitisers., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk</p>			



	management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma.			
Diphenylmethanediisocyanate, isomers and homologues	9016-87-9	TWA	0,02 mg/m3 (NCO)	GB EH40
Further information	Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological, irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even to tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. 54 Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified asthmagens or respiratory sensitisers., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma.			
		STEL	0,07 mg/m3 (NCO)	GB EH40
Further information	Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological, irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even to tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. 54 Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified asthmagens or respiratory sensitisers., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may			



	cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma.
--	---

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
4,4'-methylenediphenyl diisocyanate	101-68-8	urinary diamine (Isocyanates): 1 µmol/mol creatinine (Urine)	Post task	GB EH40 BAT
Diphenylmethanediisocyanate, isomers and homologues	9016-87-9	urinary diamine (Isocyanates): 1 µmol/mol creatinine (Urine)	Post task	GB EH40 BAT

8.2 Exposure controls

Personal protective equipment

- Eye protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water

- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (0,4 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.

- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

- Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in par-



ticular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. Ensure adequate ventilation, especially in confined areas.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : brown

Odour : very faint

Odour Threshold : No data available

pH : No data available

Melting point/range / Freezing point : No data available

Boiling point/boiling range : > 300 °C

Flash point : > 130 °C
Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : 0,01 hPa

Relative vapour density : No data available

Density : 1,16 g/cm³ (20 °C)

Solubility(ies)
Water solubility : insoluble



Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	> 600 °C
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	220 mPa.s
Viscosity, kinematic	:	> 20,5 mm ² /s (40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if inhaled.



Components:

4,4'-methylenediphenyl diisocyanate:

Acute inhalation toxicity : Acute toxicity estimate: 1,5 mg/l
Test atmosphere: dust/mist
Method: Expert judgement

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 1,5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9.400 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.



SECTION 12: Ecological information

12.1 Toxicity

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l
Exposure time: 96 h

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): > 1.640 mg/l
Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.



Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 08 05 01* waste isocyanates

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (= > 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pol- : Not applicable



lutants

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
4,4'-methylenediphenyl diisocyanate (Number on list 56)
Diphenylmethanediisocyanate, isomers and homologues (Number on list 56)
Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl) phenyl isocyanate

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Not applicable

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations
Health and Safety at Work Act 1974 & Subsidiary Regulations
Control of Substances Hazardous to Health Regulations (COSHH)
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.



- H319 : Causes serious eye irritation.
- H332 : Harmful if inhaled.
- H334 : May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 : May cause respiratory irritation.
- H351 : Suspected of causing cancer.
- H373 : May cause damage to organs through prolonged or repeated exposure.
- H373 : May cause damage to organs through prolonged or repeated exposure if inhaled.

Full text of other abbreviations

- Acute Tox. : Acute toxicity
- Carc. : Carcinogenicity
- Eye Irrit. : Eye irritation
- Resp. Sens. : Respiratory sensitisation
- Skin Irrit. : Skin irritation
- Skin Sens. : Skin sensitisation
- STOT RE : Specific target organ toxicity - repeated exposure
- STOT SE : Specific target organ toxicity - single exposure
- GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
- GB EH40 BAT : UK. Biological monitoring guidance values
- GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
- GB EH40 / STEL : Short-term exposure limit (15-minute reference period)
- ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
- CAS : Chemical Abstracts Service
- DNEL : Derived no-effect level
- EC50 : Half maximal effective concentration
- GHS : Globally Harmonized System
- IATA : International Air Transport Association
- IMDG : International Maritime Code for Dangerous Goods
- LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
- LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
- MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
- OEL : Occupational Exposure Limit
- PBT : Persistent, bioaccumulative and toxic
- PNEC : Predicted no effect concentration
- REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
- SVHC : Substances of Very High Concern
- vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Acute Tox. 4 H332

Classification procedure:

Calculation method



Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

GB / EN