Printing date 23.04.2020 Version No. 8 Revision: 23.04.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: UZIN PE 480 Comp. A
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No special requirements.
- · Sector of Use

SU19 Building and construction work

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) For professional use only.

- · Product category PC1 Adhesives, sealants
- · Application of the substance / the mixture 2-Component Epoxy Moisture Barrier (Component A)
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Producer:

UZIN UTZ AG

Dieselstraße 3

D-89079 Ulm

Phone.: +49 (0)731 4097-0

Fax: +49 (0)731 4097-110

Supplier in the UK:

Uzin Utz UK Ltd.

Unit 2, Mitchell Court

Central Park, Rugby

Warwickshire, CV23 0UY,

Telephone +44 (0) 1788 530 080

Fax +44 (0) 1788 536508

Email info@uk.uzin-utz.com

· Further information obtainable from:

Product safety department email: msds.info@uzin-utz.com

· 1.4 Emergency telephone number:

Medical emergencies (GIZ-Nord Poisons Center): +49 551 19240

Transportation emergencies: +49 621 60 43 333

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms GHS07, GHS09

(Contd. on page 2)

Trade name: UZIN PE 480 Comp. A

(Contd. of page 1)

· Signal word Warning

Hazard-determining components of labelling:

Bisphenol-A-epoxy resin (average molecular weight \leq 700) Bisphenol-F-epoxy resin (average molecular weight \leq 700)

alkyl C12-C14 glycidyl ether

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 1675-54-3 EINECS: 216-823-5 Reg.nr.: 01-2119456619-26	Bisphenol-A-epoxy resin (average molecular weight ≤700) �� Aquatic Chronic 2, H411; �� Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	25-50%
CAS: 9003-36-5 Reg.nr.: 01-2119454392-40	Bisphenol-F-epoxy resin (average molecular weight ≤700) ♠ Aquatic Chronic 2, H411; ♠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	25-50%
CAS: 68609-97-2 EINECS: 271-846-8 Reg.nr.: 01-2119485289-22	alkyl C12-C14 glycidyl ether Skin Irrit. 2, H315; Skin Sens. 1, H317	10-<20%
CAS: 17557-23-2 EINECS: 241-536-7 Reg.nr.: 01-2120759332-55	1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	5-<10%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions

(Contd. on page 3)

Printing date 23.04.2020 Version No. 8 Revision: 23.04.2020

Trade name: UZIN PE 480 Comp. A

(Contd. of page 2)

· 4.3 Indication of any immediate medical attention and special treatment needed Also observe the safety data sheet of component B.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

 CO_2 powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Wear suitable protective clothing, gloves and eye/face protection.

Immediately remove all soiled and contaminated clothing

Avoid contact with the eyes and skin.

Keep away from foodstuffs, beverages and feed.

Prevent formation of aerosols.

Wash hands before breaks and at the end of work.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from humidity and water.

Protect from frost.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

Trade name: UZIN PE 480 Comp. A

(Contd. of page 3)

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Avoid contact with the eyes and skin.

Wear suitable protective clothing, gloves and eye/face protection.

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

- · Respiratory protection: Not necessary. Ensure that room is well-ventilated during processing.
- Protection of hands:



Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability (EN 374)

· Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 *mm*

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

At least 480 minutes.

· Eye protection:



Tightly sealed goggles or face protection (EN 166)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical propert	· 9.1 In	iformation of	ı basic	physical	and	chemical	propertion
--	----------	---------------	---------	----------	-----	----------	------------

· General Information

· Appearance:

Form: Fluid Colour: Yellowish

• Odour: Weak, characteristic• Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. **Initial boiling point and boiling range:** Undetermined.

· Flash point: >100 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: >200 °C

• **Decomposition temperature:** Not determined.

· Auto-ignition temperature: Product is not selfigniting.

(Contd. on page 5)

Trade name: UZIN PE 480 Comp. A

		(Contd. of page 4
· Explosive properties:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapour pressure:	Not determined.	
· Density at 20 °C:	1.1 g/cm^3	
· Relative density	Not determined.	
· Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic at 20 °C:	400 mPas	
Kinematic:	Not determined.	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions

May produce violent reactions with bases and numerous organic substances including alcohols and amines. Exothermic polymerisation.

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Irritant gases/vapours

At elevated temperatures hazardous decomposition products such as carbon dioxide, carbon monoxide, smoke or nitric oxids may be evolved.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 23.04.2020 Version No. 8 Revision: 23.04.2020

Trade name: UZIN PE 480 Comp. A

(Contd. of page 5)

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 1675-54-3 Bisphenol-A-epoxy resin (average molecular weight ≤700)

EC50/48h 1.8 mg/l (Daphnia magna)

EC50/72h 11 mg/l (Scenedesmus capricornutum)

LC50/96h 2 mg/l (Piscis)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Toxic for aquatic organisms

Also poisonous for fish and plankton in water bodies.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

The product contains materials that are harmful to the environment.

Do not allow product to reach ground water, water course or sewage system.

Disposal should be in accordance with local, state or national legislation.

- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· 14.1 UN-Number · ADR, IMDG, IATA	UN3082
· 14.2 UN proper shipping name	
· ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANC
	LIQUID, N.O.S. (Epoxy resins)
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANC
	LIQUID, N.O.S. (Epoxy resins), MARINE POLLUTANT
· IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANC
	LIQUID, N.O.S. (Epoxy resins)

(Contd. on page 7)

Printing date 23.04.2020 Version No. 8 Revision: 23.04.2020

Trade name: UZIN PE 480 Comp. A

(Contd. of page 6) · 14.3 Transport hazard class(es) · ADR, IMDG, IATA · Class 9 Miscellaneous dangerous substances and articles. · Label · 14.4 Packing group · ADR, IMDG, IATA III14.5 Environmental hazards: · Marine pollutant: Yes Symbol (fish and tree) Symbol (fish and tree) · Special marking (ADR): Symbol (fish and tree) · Special marking (IATA): · 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and articles. 90 · Danger code (Kemler): F-A,S-F· EMS Number: · Stowage Category A· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code *Not applicable.* · Transport/Additional information: · Limited quantities (LQ) 5L· Transport category 3 · Tunnel restriction code · UN "Model Regulation": UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESINS), 9, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 8)

Trade name: UZIN PE 480 Comp. A

(Contd. of page 7)

H412 Harmful to aquatic life with long lasting effects.

· Recommended restriction of use For professional use only.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing SDS: Product safety department

· Contact:

Dr. M. Zieger, phone +49 (0)731 4097 207

E-Mail: msds.info@uzin-utz.com

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· * Data compared to the previous version altered.

GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: UZIN PE 480 Comp. B
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No special requirements.
- · Sector of Use

SU19 Building and construction work

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) For professional use only.

- · Product category PC1 Adhesives, sealants
- · Application of the substance / the mixture 2-Component Epoxy Moisture Barrier (Component B)
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Producer:

UZIN UTZ AG

Dieselstraße 3

D-89079 Ulm

Phone.: +49 (0)731 4097-0

Fax: +49 (0)731 4097-110

Supplier in the UK:

Uzin Utz UK Ltd.

Unit 2, Mitchell Court

Central Park, Rugby

Warwickshire, CV23 0UY,

Telephone +44 (0) 1788 530 080

Fax +44 (0) 1788 536508

Email info@uk.uzin-utz.com

· Further information obtainable from:

Product safety department email: msds.info@uzin-utz.com

· 1.4 Emergency telephone number:

Medical emergencies (GIZ-Nord Poisons Center): +49 551 19240

Transportation emergencies: +49 621 60 43 333

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



(Contd. on page 2)

Printing date 23.04.2020 Version No. 9 Revision: 23.04.2020

Trade name: UZIN PE 480 Comp. B

(Contd. of page 1)

Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms GHS05, GHS07, GHS09
- · Signal word Danger

· Hazard-determining components of labelling:

Tall-oil fatty acids oligomeric reaction products with triethylenetriamine and glycidyl tolyl ether Polyoxypropylenediamine

m-phenylenebis(methylamine)

· Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

	Tall-oil fatty acids oligomeric reaction products with	25-50%
Reg.nr.: 01-2120769104-56	triethylenetriamine and glycidyl tolyl ether	
	Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Skin Sens. 1, H317	
CAS: 9046-10-0	Polyoxypropylenediamine	10-<20%
Reg.nr.: 01-2119557899-12	Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Chronic 3, H412	
CAS: 61788-44-1	Phenol, styrenated	10-<20%
EINECS: 262-975-0	🕸 Aquatic Chronic 2, H411; 아 Skin Irrit. 2, H315; Skin Sens. 1,	
Reg.nr.: 01-2119980970-27	H317	
CAS: 1477-55-0	m-phenylenebis(methylamine)	10-<20%
	♦ Skin Corr. 1B, H314; ♦ Acute Tox. 4, H302; Acute Tox. 4,	
Reg.nr.: 01-2119480150-50	H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412	
CAS: 2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	5-<10%
	📀 Skin Corr. 1B, H314; 🗘 Acute Tox. 4, H302; Acute Tox. 4,	
Reg.nr.: 01-2119514687-32	H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	
CAS: 90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	5-<10%
EINECS: 202-013-9	📀 Skin Corr. 1B, H314; Eye Dam. 1, H318; 🗘 Acute Tox. 4, H302	
Reg.nr.: 01-2119560597-27		

Trade name: UZIN PE 480 Comp. B

		(Cor	ntd. of page 2)
	CAS: 10563-29-8	N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine	3-<5%
	EINECS: 234-148-4 Reg.nr.: 01-2119970376-29	📀 Skin Corr. 1A, H314; 🕔 Acute Tox. 4, H302; Skin Sens. 1B, H317	
	CAS: 112-53-8	Lauryl alcohol	3-<5%
	EINECS: 203-982-0 Reg.nr.: 01-2119485976-15	Aquatic Acute 1, H400; Aquatic Chronic 2, H411; 🕠 Eye Irrit. 2, H319	
Ī	CAS: 919-30-2	3-aminopropyltriethoxysilane	<0.5%
	EINECS: 213-048-4 Reg.nr.: 01-2119480479-24	Skin Corr. 1B, H314; 🗘 Acute Tox. 4, H302; Skin Sens. 1, H317	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO₂ powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Wear suitable protective clothing, gloves and eye/face protection.

(Contd. on page 4)

Printing date 23.04.2020 Version No. 9 Revision: 23.04.2020

Trade name: UZIN PE 480 Comp. B

(Contd. of page 3)

Immediately remove all soiled and contaminated clothing

Avoid contact with the eyes and skin.

Keep away from foodstuffs, beverages and feed.

Prevent formation of aerosols.

Wash hands before breaks and at the end of work.

- · Information about fire and explosion protection: Keep ignition sources away Do not smoke.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Protect from frost.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Avoid contact with the eyes and skin.

Wear suitable protective clothing, gloves and eye/face protection.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

- · Respiratory protection: Not necessary. Ensure that room is well-ventilated during processing.
- Protection of hands:



Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability (EN 374)

· Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

At least 480 minutes.

· Eye protection:



Tightly sealed goggles or face protection (EN 166)

GB

Printing date 23.04.2020 Version No. 9 Revision: 23.04.2020

Trade name: UZIN PE 480 Comp. B

(Contd. of page 4)

9.1 Information on basic physical and of	chemical properties
General Information	
Appearance: Form:	Fluid
Colour:	Yellow
Odour:	Fish-like
Odour threshold:	Not determined.
pH-value at 20°C:	11
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	2: Undetermined.
Flash point:	>100 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	>200 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	1.1 g/cm^3
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability

· 9.2 Other information

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

No further relevant information available.

- · 10.3 Possibility of hazardous reactions Strong exothermic reaction with acids.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Corrosive gases/vapours

At elevated temperatures hazardous decomposition products such as carbon dioxide, carbon monoxide, smoke or nitric oxids may be evolved.

Printing date 23.04.2020 Version No. 9 Revision: 23.04.2020

Trade name: UZIN PE 480 Comp. B

(Contd. of page 5)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 1	· LD/LC50 values relevant for classification:		
CAS: 9046	CAS: 9046-10-0 Polyoxypropylenediamine		
Inhalative	LC50/4 h	1.48 mg/l (rat)	
CAS: 1477	CAS: 1477-55-0 m-phenylenebis(methylamine)		
Oral	LD50	930 mg/kg (rat)	
Dermal	LD50	3,100 mg/kg (rabbit)	
Inhalative	LC50/4 h	1.34 mg/l (rat)	
CAS: 2855	CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine		
Oral	LD50	1,030 mg/kg (rat) (OECD 401)	
Dermal	LD50	1,840 mg/kg (rabbit)	
Inhalative	LC50/4 h	>5 mg/l (rat)	
CAS: 112-	53-8 Laur _:	yl alcohol	
Oral	LD50	12,800 mg/kg (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 1628940-03-3 Tall-oil fatty acids oligomeric reaction products with triethylenetriamine and glycidyl tolyl ether

EL50/72h | 0.25 mg/l (Pseudokirchneriella subcapitata)

CAS: 112-53-8 Lauryl alcohol

LC50/96h >100 mg/l (Leuciscus idus)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Very toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Very toxic for aquatic organisms

(Contd. on page 7)

Printing date 23.04.2020 Version No. 9 Revision: 23.04.2020

Trade name: UZIN PE 480 Comp. B

(Contd. of page 6)

Also poisonous for fish and plankton in water bodies.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

The product contains materials that are harmful to the environment.

Do not allow product to reach ground water, water course or sewage system.

Disposal should be in accordance with local, state or national legislation.

- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

14.1 UN-Number ADR, IMDG, IATA	UN2735
· 14.2 UN proper shipping name · ADR	2735 POLYAMINES, LIQUID, CORROSIVE, N.O. (Polyoxypropylenediamine, m-phenylenebis(methylamine, ENVIRONMENTALLY HAZARDOUS
· IMDG	POLYAMINES, LIQUID, CORROSIVE, N.O. (Polyoxypropylenediamine, m-phenylenebis(methylamine, MARINE POLLUTANT
· IATA	POLYAMINES, LIQUID, CORROSIVE, N.O. (Polyoxypropylenediamine, m-phenylenebis(methylamine,
· 14.3 Transport hazard class(es)	
· ADR, IMDG	
Y Y	
· Class	8 Corrosive substances.
· Label	8
· IATA	
· Class	8 Corrosive substances.
· Label	8
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	Product contains environmentally hazardous substance Fatty acids, tall-oil, reaction products wi triethylenetriamine

Trade name: UZIN PE 480 Comp. B

	(Contd. of page
· Marine pollutant:	Yes
	Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Corrosive substances.
Danger code (Kemler):	80
EMS Number:	F- A , S - B
· Segregation groups	Alkalis
· Stowage Category	A
· Segregation Code	SG35 Stow "separated from" SGG1-acids
· 14.7 Transport in bulk according to Ann Marpol and the IBC Code	ex II of Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	IL
· Transport category	2
· Tunnel restriction code	E
· UN "Model Regulation":	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O (POLYOXYPROPYLENEDIAMINE, M
	PHENYLENEBIS (METHYLAMINE)), 8, I. ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Recommended restriction of use For professional use only.

(Contd. on page 9)

Trade name: UZIN PE 480 Comp. B

(Contd. of page 8)

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing SDS: Product safety department

· Contact:

Dr. M. Zieger, phone +49 (0)731 4097 207

E-Mail: msds.info@uzin-utz.com

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1A: Skin corrosion/irritation - Category 1A

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

 $\label{eq:Adjustic} \textit{Acute 1: Hazardous to the aquatic environment - acute aquatic hazard-Category~1}$

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· * Data compared to the previous version altered.

GB