

Ecoline Additive Pitch Black

Technical Data Sheet
June 2022
Page 1/1



Ecoline



- » Additive for our [Ecoline MultiTop^{plus} system](#)
- » **black surface**
- » **structure of the wood and laying system still visible**

Product characteristics:

One can accomplish a black surface with extraordinary effect. The structure of the wood and the laying system is still visible. DIBt approval Z-157.10-162

Article number:

9918Eco Pitch Black

Fields of application:

For all wood and bamboo floors (solid wood flooring, parquet, and multi-layer flooring) and interior surfaces. Trial coating recommended.

Hint:

For the application of tropical wood species, thermally or chemically treated wood we recommend our [Ecoline Oil Ground Coat 3490Eco Ebony](#).

Please also have a look at the Technical Data Sheet Ecoline MultiTop^{plus} System for further technical information.

Preparation:

Switch off the underfloor heating 36 h before application. Switch it back on 24 h after applying the last coat.

Hint:

Do not pour *Additive Ecoline Pitch Black* directly on the surface; rather work with a Paint Tray. Pour *Additive Ecoline Pitch Black* into [Ecoline MultiTop](#) lacquer and shake well two minutes. Let rest for 5 minutes and shake anew.

Preparation:

First coat: apply [Ecoline MultiTop](#) with *Additive Pitch Black* rapidly with [SAICOS Aqua Roller](#).

Application quantity: approx. 100 - 120 g/sqm.

Drying time: approx. 3 - 4 hours.

Second coat: apply [Ecoline MultiTop](#) with *Additive Pitch Black* rapidly with [SAICOS Aqua Roller](#).

Application quantity: approx. 100 - 120 g/sqm.

Drying time: approx. 3 - 4 hours.

Important: Maximum two lacquer coats per day.

In-between-sanding:

after 6 hours with 120 - 150 grit, remove sanding dust with dry cloth or vacuum cleaner.

Third coat: apply [Ecoline MultiTop](#) with *Additive Pitch Black* rapidly with [SAICOS Aqua Roller](#).

Application quantity: approx. 100 - 120 g/sqm.

Drying time: approx. 8 hours.

Coverage:

Application with [SAICOS Aqua Roller](#), Application quantity 100 - 120 g/sqm. 0,45 liter of supplement for 4,55 liter [Ecoline MultiTop](#). 5 liters are sufficient for about 45 sqm (one coat). Coverage depends on wood species and surface structure.

Storage:

In unopened / sealed container at least 1 year. The liquid product is susceptible to frost. Frost-free transport and store (> 5 ° C).

Safety Instructions – First Aid:

Keep out of the reach of children. Do not fill into food, beverage or other containers used for foodstuffs.

Contains: BIT.

May produce an allergic reaction.

Safety data sheet available on request.

EU limit for two component lacquer (Cat A/j): 140 g / l (2010) *SAICOS Ecoline MultiTop* with supplement *Ecoline Pitch Black* contains max. 140 g / l VOC.

Our application advice is provided to the best of our knowledge and based on experiments, however, applies only as a non-binding recommendation and does not exempt you from testing the products supplied by us as to their suitability for the intended purpose. Since the application and processing of the products is beyond our control, the responsibility rests solely with the user. With publishing a new technical data sheet the previous loses its validity.

SAICOS COLOUR GmbH

Carl-Zeiss-Str. 3

D-48336 Sassenberg

☎ +49 2583 3037-0

☎ +49 2583 3037-10

info@saicos.de

www.saicos.de