

Trade name: Treatex Hardwax Oil ULTRA Clear Flatt Matt 210

Version: 3 / GB

Revision: 09.02.2018

Replaces Version: 2 / GB

Print date: 13.03.18

## 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Treatex Hardwax Oil ULTRA Clear Flatt Matt 210

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Surface treatment of wood and other materials

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Treatex Ltd. Unit i, Howland Road business Park  
Howland Road, Thame, Oxfordshire,  
OX9 3GQ

Telephone no. +44 (0) 1844 260416

Fax no. +44 (0) 1844 358160

E-mail address info@treatex.co.uk

### 1.4. Emergency telephone number

Germany: +49 (0) 30 30686700

## 2. Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)  
Aquatic Chronic 4 H413

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008  
For explanation of abbreviations see section 16.

### 2.2. Label elements

#### Labelling according to regulation (EC) No 1272/2008

##### Hazard statements

H413 May cause long lasting harmful effects to aquatic life.

##### Precautionary statements

P273 Avoid release to the environment.

P501.9 Dispose of contents/container as problematic waste.

#### Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

##### Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

##### Further supplemental information

Cleaning cloth soaked with the product can self ignite during packing up, therefore dry the cloth on a line or through spreading and dispose of after dry up.

### 2.3. Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB) (if not listed in Section 3).

Trade name: Treatex Hardwax Oil ULTRA Clear Flatt Matt 210

Version: 3 / GB

Revision: 09.02.2018

Replaces Version: 2 / GB

Print date: 13.03.18

### 3. Composition/information on ingredients

#### Hazardous ingredients (Regulation (EC) No. 1272/2008)

##### hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

CAS No.	64742-48-9				
Registration no.	01-2119457273-39				
Concentration	>= 25	<	50		%

Classification (Regulation (EC) No. 1272/2008)	
Asp. Tox. 1	H304

##### alkanes, C11-14-iso-

CAS No.	90622-58-5				
Concentration	>= 25	<	30		%

Classification (Regulation (EC) No. 1272/2008)	
Asp. Tox. 1	H304
Aquatic Chronic 4	H413
	EUH066

##### alkanes, C11-13-iso-

CAS No.	90622-58-5				
EINECS no.	920-901-0				
Registration no.	01-2119456810-40				
Concentration	>= 1	<	10		%

Classification (Regulation (EC) No. 1272/2008)	
Asp. Tox. 1	H304
	EUH066

##### 2-ethylhexanoic acid zirconium salt

CAS No.	22464-99-9				
EINECS no.	245-018-1				
Registration no.	01-2119979088-21				
Concentration	>= 0,1	<	1		%

Classification (Regulation (EC) No. 1272/2008)	
Repr. 2	H361d

For explanation of abbreviations see section 16.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) (if not listed in Section 3).

### 4. First aid measures

#### 4.1. Description of first aid measures

##### General information

In all cases of doubt, or when symptoms persist, seek medical attention. If unconscious place in recovery position and seek medical advice. First aider: Pay attention to self-protection! Remove affected person from danger area, lay him down.

Trade name: Treatex Hardwax Oil ULTRA Clear Flatt Matt 210

Version: 3 / GB

Revision: 09.02.2018

Replaces Version: 2 / GB

Print date: 13.03.18

#### **After inhalation**

In case of accident by inhalation: remove casualty to fresh air and keep at rest. Keep warm, calm and covered up. In all cases of doubt, or when symptoms persist, seek medical attention.

#### **After skin contact**

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

#### **After eye contact**

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

#### **After ingestion**

Do not induce vomiting. Take medical treatment.

### **4.2. Most important symptoms and effects, both acute and delayed**

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. High concentration of vapours may cause irritation to eyes and respiratory system and produce narcotic effects.

### **4.3. Indication of any immediate medical attention and special treatment needed**

#### **Hints for the physician / treatment**

Treat symptomatically.

## **5. Firefighting measures**

### **5.1. Extinguishing media**

#### **Suitable extinguishing media**

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist

#### **Non suitable extinguishing media**

Do not use a solid water stream as it may scatter and spread fire.

### **5.2. Special hazards arising from the substance or mixture**

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard. Vapours can form an explosive mixture with air.

### **5.3. Advice for firefighters**

#### **Special protective equipment for fire-fighting**

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

#### **Other information**

Do not allow run-off from fire fighting to enter drains or water courses. Cool closed containers exposed to fire with water. Standard procedure for chemical fires.

## **6. Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Do not inhale vapours. Do not inhale gases. Do not inhale mist.

### **6.2. Environmental precautions**

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Trade name: Treatex Hardwax Oil ULTRA Clear Flatt Matt 210

Version: 3 / GB

Revision: 09.02.2018

Replaces Version: 2 / GB

Print date: 13.03.18

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

## 7. Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep container tightly closed and dry in a cool, well-ventilated place. Use only with adequate ventilation/personal protection. Ensure adequate ventilation. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

#### Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Vapours are heavier than air and may spread along floors. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Take measures to prevent the build up of electrostatic charge. Wear shoes with conductive soles. No sparking tools should be used. Fight fire with normal precautions from a reasonable distance. Do not process in the same cabin together with highly flammable material (e.g. CN lacquer) => fire hazard through self ignition! Cleaning cloth soaked with the product can self ignite during packing up, therefore dry the cloth on a line or through spreading and dispose of after dry up.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Provide solvent-resistant and impermeable floor. Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

#### Further information on storage conditions

Keep away from heat. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

### 7.3. Specific end use(s)

See exposure scenario, if available.

## 8. Exposure controls/personal protection

### 8.1. Control parameters

#### Other information

Trade name: Treatex Hardwax Oil ULTRA Clear Flatt Matt 210

Version: 3 / GB

Revision: 09.02.2018

Replaces Version: 2 / GB

Print date: 13.03.18

### Derived No/Minimal Effect Levels (DNEL/DMEL)

#### Silica, amorphous, fumed, cryst.-free

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	4	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	4	mg/m <sup>3</sup>

## 8.2. Exposure controls

### Exposure controls

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### Respiratory protection

Respiratory protection not applicable; Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

### Hand protection

Protective gloves complying with EN 374.

Glove material

Appropriate Material                      Nitrile rubber

Material thickness                      >= 0,4                      mm

Breakthrough time                      >= 30                      min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### Eye protection

Wear eye glasses with side protection according to EN 166.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## 9. Physical and chemical properties

Trade name: Treatex Hardwax Oil ULTRA Clear Flatt Matt 210

Version: 3 / GB

Revision: 09.02.2018

Replaces Version: 2 / GB

Print date: 13.03.18

**9.1. Information on basic physical and chemical properties**

<b>Form</b>	liquid
<b>Colour</b>	colourless
<b>Odour</b>	characteristic
<b>Odour threshold</b>	
Remarks	not determined
<b>pH value</b>	
Remarks	not determined
<b>Melting point</b>	
Remarks	not determined
<b>Freezing point</b>	
Remarks	not determined
<b>Initial boiling point and boiling range</b>	
Remarks	not determined
<b>Flash point</b>	
Value	> 60 °C
<b>Evaporation rate</b>	
Remarks	not determined
<b>Flammability (solid, gas)</b>	
not determined	
<b>Upper/lower flammability or explosive limits</b>	
Remarks	not determined
<b>Vapour pressure</b>	
Remarks	not determined
<b>Vapour density</b>	
Remarks	not determined
<b>Density</b>	
Value	appr. 0,88 kg/l
Temperature	20 °C
<b>Solubility in water</b>	
Remarks	not determined
<b>Solubility(ies)</b>	
Remarks	not determined
<b>Partition coefficient: n-octanol/water</b>	
Remarks	not determined
<b>Ignition temperature</b>	
Remarks	not determined
<b>Decomposition temperature</b>	
Remarks	not determined
<b>Viscosity</b>	
Remarks	not determined
<b>Efflux time</b>	

Trade name: Treatex Hardwax Oil ULTRA Clear Flatt Matt 210

Version: 3 / GB

Revision: 09.02.2018

Replaces Version: 2 / GB

Print date: 13.03.18

Value	40	to	50	s
Temperature	20	°C		
Method	DIN 53211 4 mm			

**Explosive properties**

evaluation not determined

**Oxidising properties**

Remarks not determined

**9.2. Other information****Non-volatile content**

Value	41,7	%
Method	calculated value	

**Other information**

This information is not available.

**10. Stability and reactivity****10.1. Reactivity**

Stable under recommended storage and handling conditions (see section 7).

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

To avoid thermal decomposition, do not overheat.

**10.4. Conditions to avoid**

Isolate from sources of heat, sparks and open flame.

**Decomposition temperature**

Remarks not determined

**10.5. Incompatible materials**

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**10.6. Hazardous decomposition products**Carbon monoxide and carbon dioxide, nitrous oxides (NO<sub>x</sub>), dense black smoke, No decomposition if used as prescribed.**11. Toxicological information****11.1. Information on toxicological effects****Acute oral toxicity**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

**Acute dermal toxicity**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

**Acute inhalational toxicity**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Trade name: Treatex Hardwax Oil ULTRA Clear Flatt Matt 210

Version: 3 / GB

Revision: 09.02.2018

Replaces Version: 2 / GB

Print date: 13.03.18

**Skin corrosion/irritation**

Method Calculation method (Regulation (EC) No. 1272/2008)  
 Remarks Based on available data, the classification criteria are not met.

**Serious eye damage/irritation**

Method Calculation method (Regulation (EC) No. 1272/2008)  
 Remarks Based on available data, the classification criteria are not met.

**Sensitization**

Method Calculation method (Regulation (EC) No. 1272/2008)  
 Remarks Based on available data, the classification criteria are not met.

**Sensitization (Components)**

**uaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, stearates, salts with bentonite**  
 evaluation No sensitizing effects known.

**Mutagenicity**

Method Calculation method (Regulation (EC) No. 1272/2008)  
 Remarks Based on available data, the classification criteria are not met.

**Reproductive toxicity**

Method Calculation method (Regulation (EC) No. 1272/2008)  
 Remarks Based on available data, the classification criteria are not met.

**Carcinogenicity**

Method Calculation method (Regulation (EC) No. 1272/2008)  
 Remarks Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity (STOT)**

Method Calculation method (Regulation (EC) No. 1272/2008)  
 Remarks Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Other information**

No toxicological data are available.

**12. Ecological information**

**12.1. Toxicity**

**General information**

For this subsection there is no ecotoxicological data available on the product as such.

**Fish toxicity (Components)**

**alkanes, C11-13-iso-**  
 Species Fish  
 LC50/EC50/IC50/LL50/EL5 > 100 mg/l  
 0  
 Duration of exposure = 96 h

**Daphnia toxicity (Components)**

**alkanes, C11-14-iso-**  
 Species Daphnia magna (Water flea)  
 EC50 > 1000 mg/l



Trade name: Treatex Hardwax Oil ULTRA Clear Flatt Matt 210

Version: 3 / GB

Revision: 09.02.2018

Replaces Version: 2 / GB

Print date: 13.03.18

Duration of exposure 48 h

## 12.2. Persistence and degradability

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Biodegradability (Components)

**alkanes, C11-14-iso-**  
evaluation Not readily biodegradable.

**alkanes, C11-13-iso-**  
evaluation Not readily biodegradable.

## 12.3. Bioaccumulative potential

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Partition coefficient: n-octanol/water

Remarks not determined

## 12.4. Mobility in soil

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Mobility in soil

no data available

## 12.5. Results of PBT and vPvB assessment

### General information

For this subsection there is no ecotoxicological data available on the product as such.

## 12.6. Other adverse effects

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### General information / ecology

For this subsection there is no ecotoxicological data available on the product as such.

## 13. Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations for the product

EWC waste code	080111 - waste paint and varnish containing organic solvents or other dangerous substances
EWC waste code	200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter drains or waterways.

#### modified product

EWC waste code	080113 - sludges from paint or varnish containing organic solvents or other dangerous substances
EWC waste code	080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

Trade name: Treatex Hardwax Oil ULTRA Clear Flatt Matt 210

Version: 3 / GB

Revision: 09.02.2018

Replaces Version: 2 / GB

Print date: 13.03.18

### Dried residues

EWC waste code 080112 - waste lacquers and waste paint except those falling under 080111

### Disposal recommendations for packaging

EWC waste code 150110 - packaging containing residues of or contaminated by dangerous substances

Completely emptied packagings can be given for recycling.  
Germany: KBS system for sheet covering

## 14. Transport information

### Land transport ADR/RID

Not classified as dangerous in the meaning of transport regulations.

### Marine transport IMDG/GGVSee

Not classified as dangerous in the meaning of sea and air transport regulations.

### Air transport ICAO/IATA

Not a dangerous substance as defined in the above regulations.

## 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Water Hazard Class (Germany)

Water Hazard Class (Germany) WGK 1

Remarks Derivation of WGK according to Annex 1 No. 5.2 AwSV

#### VOC

VOC (EU) 58,1 % 512 g/l

### 15.2. Chemical safety assessment

For this substance / mixture a chemical safety assessment was not carried out.

## 16. Other information

### Hazard statements listed in Chapter 3

EUH066 Repeated exposure may cause skin dryness or cracking.  
H304 May be fatal if swallowed and enters airways.  
H361d Suspected of damaging the unborn child.  
H413 May cause long lasting harmful effects to aquatic life.

### CLP categories listed in Chapter 3

Aquatic Chronic 4 Hazardous to the aquatic environment, chronic, Category 4  
Asp. Tox. 1 Aspiration hazard, Category 1  
Repr. 2 Reproductive toxicity, Category 2

### Abbreviations

ADR - Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID - Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IMDG - International Maritime Code for Dangerous Goods

Trade name: Treatex Hardwax Oil ULTRA Clear Flatt Matt 210

Version: 3 / GB

Revision: 09.02.2018

Replaces Version: 2 / GB

Print date: 13.03.18

IATA - International Air Transport Association

IATA-DGR - Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO-TI - Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS - Globally Harmonized System of Classification and Labelling of Chemicals

EINECS - European Inventory of Existing Commercial Chemical Substances

CAS - Chemical Abstracts Service (division of the American Chemical Society)

GefStoffV - Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL - Lowest Observed Adverse Effect Level

LOEL - Lowest Observed Effect Level

NOAEL - No Observed Adverse Effect Level

NOEC - No Observed Effect Concentration

NOEL - No Observed Effect Level

OECD - Organisation for Economic Cooperation and Development

VOC - Volatile Organic Compounds

Changes since the last version are highlighted in the margin (\*\*\*). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.