

Cleaner

CLEAN

Water-based cleaning agent for flooring

SUITABLE FOR:

- routine cleaning of:
 - ▶ sealed wood/cork floors
 - ▶ oiled and waxed hardwood floors
 - ▶ Linoleum
 - ▶ PVC
 - ▶ natural and synthetic stone floors
- deep cleaning of:
 - ▶ with PALLMANN products oiled and waxed hardwood floors



PRODUCT BENEFITS / PROPERTIES:

- ▶ fast drying

TECHNICAL DATA:

Packaging:	plastic container
Packsize:	0,75 and 10 l
Shelf life:	at least 24 months
Consumption:	Routine cleaning: approx. 50 - 100 ml/5l water Deep cleaning: approx. 200 ml/5l water until pure*
Working climate:	between 18 – 25 °C and 35 – 65 % relative humidity

*The mixing ratio depends on the degree of soiling from 200 ml to 5 litres of water, until pure application.

SURFACE PREPARATION:

Remove traces of dirt and dust by using the PALLMANN MOP, broom or vacuum cleaner. In case of heavy surface soiling, an intensive clean must be carried out.

APPLICATION:

Routine cleaning:

1. Before use, the container must be brought to room temperature (20 °C) and must be shaken well.
2. Dilute approx. 50 - 100 ml PALLMANN CLEAN with 5 liters of water and apply using the damp (not wet) PALLMANN MOP.
3. After drying (approx. 1 hours) the surface can be put back into use.
4. The exact maintenance and care routine is shown in the respective care instruction.

Deep cleaning of PALLMANN oiled wood floors:

1. Before use, the container must be brought to room temperature (20 °C) and must be shaken well.
2. The mixing proportion of PALLMANN CLEAN depends on the level of contamination (200 ml/5 liters of water up to undiluted). Apply evenly using the damp (not wet) PALLMANN MOP to the surface to be cleaned. Leave to act 2 to max. 5 minutes.
3. Remove the dirt from the surface with a PALLMANN MOP, brush or PALLMANN UNO and CLEANING PAD GREEN.
4. After cleaning, wiping with clear water is necessarily.
5. After drying the surface can be put back into use.
6. After use, clean tools with water.
7. The thoroughly cleaned surface must be re-oiled with the respective oil/wax system (PALLMANN MAGIC OIL line).
8. The exact maintenance and care routine is shown in the respective care instruction.

IMPORTANT NOTES:

- ▶ Optimum temperature is 18 to 25 °C with the relative humidity > 35 % and < 65 %. Low temperatures and high humidity will extend the drying time. High temperatures and low humidity will shorten the drying time.
- ▶ Shelf life minimum 24 months in original packaging when stored in dry conditions. Protect from freezing and do not expose to temperatures over 40 °C.
- ▶ Tightly reseal opened containers.
- ▶ Leave freshly sealed surfaces until fully hardened before treating with PALLMANN CLEAN.
- ▶ Leave freshly oiled surfaces at least 12 hours before cleaning with PALLMANN CLEAN.
- ▶ Regular maintenance improves the appearance and increases the wear life.
- ▶ The following standards and notices are applicable and especially recommended: DIN 18356 "Working with parquet and woodblocks", DIN 18365 "Working with floor coverings".

PROTECTION OF THE WORKPLACE AND THE ENVIRONMENT:

Not flammable. Use of barrier cream and ventilation of the work area are recommended.

DISPOSAL:

Do not allow dispersal into drains, sewers or ground. Rinse containers, which have been emptied from any residues, with little water and dispose of the containers in accordance with local guidelines as recyclable packaging. Collect and reuse rinsing water and product remnants. If even necessary, dispose of containers with residues as well as product remnants as special waste.